

# **TECHNICAL DATA**

TAMPER BT 60, BT 65





Maximum reliability and longevity
All around engine protection




More transparency
Hour counter/tachometer with a
service indicator which can be reset



**Simple operation**Engine and fuel supply with combined switch

#### Shipping dimensions in cub.yd

**BT 60** 0.345 **BT 65** 0.345



### **Standard Equipment**

- -Protective engine covering -Paper air filter system with two stages
  - -Automatic oil level control -Dual fuel filter system
- Dual titler system
   ✓ Vibration insulated steering bow
   ✓ Self-cleaning air filter housing
   ✓ Protective covering
   ✓ Single point lifting device
   ✓ Recoil starter
   ✓ Place is sector as leading aid

- ✓ Plastic castor as loading aid
- ✓ Infinitely variable frequency
   ✓ Combination of engine stop/fuel
- switch

## **Optional Equipment**

- ☐ Transport device with puncture proof wheels
- ☐ Tamper foot widths (6.3-13 in)
- ☐ Tamper foot extensions
- ☐ Special painting ☐ Tool kit
- $\hfill\Box$  Service Kit
- □ Operator protection contact breaker switch

  ☐ TOUGH WARRANTY

#### Dimensions in in

В н L1 W **BT 60** 13.8 40.6 28.7 13.2 9.1 **BT 65** 13.8 40.6 28.7 13.2 11.0

Technical Data		BOMAG BT 60	BOMAG BT 65
Weights Operating weight CECE	lb lb	128 126	150 148
Dimensions Working width (tamper plate)	in	9.1	11.0
Driving Characteristics Working speed max	ft/min ft2/h	65.6 2,970.9	65.6 3,616.8
Drive Engine manufacturer Type	hp	Honda GXR 120 StageV/CARB P.3 air 1 3.8 Gasoline mech. 0.2	Honda GXR 120 StageV/CARB P.3 air 1 3.8 Gasoline mech. 0.2
Exciter system FrequencyImpact force		600.0-708.0 15.0	600.0-708.0 17.0
Capacities Fuel	gal	0.8	0.8

Technical modifications reserved. Machines may be shown with options.



**BOMAG Americas, Inc.** 125 Blue Granite Parkway Ridgeway, SC 29130 USA Tel. +1 803 3370700 Fax +1 803 3370800

www.bomag.com/us

